

ANDEROL ALL 5

High Performance Air Line Lubricant

Product Data Sheet



ANDEROL ALL 5 is a next generation synthetic compressor oil based on a mixture of specially selected synthetic polyalphaolefins combined with a high performance additive technology. This advanced formulation provides additional detergency properties preventing lacquer and varnish formation.

ANDEROL ALL 5 is designed to provide excellent lubrication to the components of pneumatic tools.

ANDEROL ALL 5 can be used as flushing fluid thanks to its low viscosity

ADVANTAGES / BENEFITS

- Compatible with compressor seals, gaskets, hoses and system components
- Reduced varnish, lacquer and deposits
- Lower oil consumption
- Excellent anti-wear properties
- Rust and oxidation inhibited
- Good water separation
- Very low sludge formation

COMPATIBILITY

ANDEROL synthetic hydrocarbon based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to an ANDEROL synthetic hydrocarbon based lubricant.

APPLICATION

Recommended for use in all sorts of pneumatic tools and as flushing fluid.
Conveyor line components
Controls
All air actuated components

PROPERTIES	TEST METHOD	ANDEROL ALL 5
Appearance @ 20°C	Visual	Clear colorless to light yellow liquid
Viscosity @ 40°C, cSt	ASTM D-445	5.5
Viscosity @ 100°C, cSt	ASTM D-445	1.8
Density @ 15°C, kg/l	ASTM D-1298	0.800
Flash Point, COC, °C	ASTM D-92	160
Pour Point, °C	ASTM D-97	-55
Demulsibility @ 54°C, min	ASTM D-1401	10

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

APPROVALS / REGISTRATIONS



ANDEROL BV

Punterweg 21 A
6222 NW MAASTRICHT
The NETHERLANDS
Tel No.: +31 (0)43 352 41 90
Fax No.: +31 (0)43 352 41 99
www.anderol-europe.com