



PRODUCT DATA SHEET

ANDEROL 6460

H1 High Performance Food Grade Gear Lubricant



ADVANTAGES/BENEFITS

- Fewer oil changes
- Reduces energy costs
- Compatible with mineral oils and most synthetic fluids
- High and low temperature applications
- Increased oxidation stability
- Reduced volatility

COMPATIBILITY

ANDEROL® synthetic hydrocarbon based lubricants are similar to mineral oils in their compatibility with paints, seals, gaskets and hoses. No special precautions related to compatibility are required when changing over from a mineral oil lubricant to an **ANDEROL®** synthetic hydrocarbon based lubricant.

APPLICATION

- Gear sets, excluding Worm Gears *)
- Bearings
- Circulating oil systems
- Chains

*) for Worm Gears **ANDEROL 7460 FG**

is recommended.

ANDEROL 6460 is a synthetic gear oil based on a mixture of specially selected non-toxic synthetic polyalphaolefins with a specially developed additive system providing excellent oxidative and thermal stability.

This product meets the lubrication requirements of gears running in food processing plants.

ANDEROL 6460 is NSF/H1 registered. The product is certified Kosher by the Orthodox Union and Halal by the Islamic Food Council of Europe.

ANDEROL® Food Grade Lubricants meet the requirement of the FDA regulation 21 CFR 178.3570.

PROPERTIES	TEST METHOD	ANDEROL 6460
ISO VG	ASTM D-2422	460
Appearance @ 20°C	visual	Clear colorless to light yellow liquid
Viscosity @ 40°C, cSt	ASTM D-445	444.3
Viscosity @ 100°C, cSt	ASTM D-445	37.5
Viscosity Index	ASTM D-2270	128
Density @ 15°C, kg/l	ASTM D-1298	0.862
Total Acid Number, mg KOH/g	ASTM D-664	0.5
Flash Point, COC, °C	ASTM D-92	245
Pour Point, °C	ASTM D-97	-39
Demulsibility@ 82°C, min.	ASTM D-1401	25
4-Ball Wear, 1200 rpm, 75°C, 40 kg	ASTM D-4172	0.32

FOR MORE INFORMATION PLEASE REFER TO THE RELEVANT MATERIAL SAFETY DATA SHEET

REGISTRATIONS



ANDEROL®
Specialty Lubricants

Groot Egtenrayseweg 23, 5928 PA Venlo, The Netherlands • Tel: +31 (0)77 3960340 • www.anderol-europe.com

This information is furnished without warranty, representation, inducement, or license of any kind except that it is accurate to the best of OUR knowledge or obtained from sources believed by ANDEROL® to be accurate. ANDEROL® does not assume any legal responsibility for use of reliance upon it. Only Chemists or chemically qualified lab technicians should carry out tests. Before using any chemicals, read its label and Material Safety Data Sheet.